





中国认可 国际互认 检测 TESTING CNAS L0599

Test Report SL52035260315601TX Date: June 15,2020 Page 1 of 9

JIANGYIN XINNI TEXTILE CO.,LTD 10 HUANXI ROAD, ZHUTANG TOWN, JIANGYIN CITY, JIANGSU PROVINCE, CHINA

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description : (A)Folding Particulate Respirator

Sample color : White

Manufacturer : JIANGYIN XINNI TEXTILE CO.,LTD Supplier : JIANGYIN XINNI TEXTILE CO.,LTD

Model : RY508-P2

Sample Receiving Date : May 06, 2020

Testing Period : May 06, 2020 - Jun 15, 2020

Test Result(s) : Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested, for further details, please refer to the following page(s).

Test Performed : Selected test(s) as requested by applicant

Conclusion:

Sample No.	Recommendation Level	
(A)	FFP2 NR	

Signed for and on behalf of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd Testing Center

Sara Guo (Account Executive)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issue defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's ersponsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



SL52035260315601TX Date: June 15,2020

Test Result

Page 2 of 9

Respiratory Protective Devices- Filtering Half Masks to Protect against Particles- Requirements, Testing, Marking

(EN 149:2001+A1:2009)

Clause 7.4 Packaging

(EN 149:2001+A1:2009 Clause 8.2)

Test Requirement	Results	Comment
Particle filtering half masks shall be offered for sale packaged in such a way that they are protected against mechanical damage and contamination	Comply	Pass
before use.		

Clause 7.5 Material*

(EN 149:2001+A1:2009, Clause 8.2 & 8.3.1 & 8.3.2)

Test Requirement	Results	Comment
Materials used shall be suitable to withstand handling and wear over the period for which the particle filtering half mask is designed to be used.	Comply	
After undergoing the conditioning described in 8.3.1 none of the particle filtering half masks shall have suffered mechanical failure of the facepiece or straps.	Comply	Pass
When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering half mask shall not collapse.	Comply	
Any material from the filter media released by the air flow through the filter shall not constitute a hazard or nuisance for the wearer.	Comply	

Clause 7.6 Cleaning and Disinfecting*

(EN 149:2001+A1:2009, Clause 8.4 & 8.5 & 8.11)

Test Requirement	Results	Comment
If the particle filtering half mask is designed to be re-usable, the materials used shall withstand the cleaning and disinfecting agents and procedures to be specified by the manufacturer. With reference to 7.9.2, after cleaning and disinfecting the re-usable particle filtering half mask shall satisfy the penetration requirement of the relevant class.	Not applicable (Not designed to be re-usable)	N.A.

Clause 7.7 Practical Performance*

(FN 149:2001+A1:2009 Clause 8.4)

Test Requirement	Results	Comment
The particle filtering half mask shall undergo practical performance tests under realistic conditions. These general tests serve the purpose of checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard.	No imperfections	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035260315601TX

Date: June 15,2020 Page 3 of 9

Clause 7.8 Finish of Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
Parts of the device likely to come into contact with the wearer shall have no	No sharp edges	Pass
sharp edges or burrs.	or burrs	Fa55

Clause 7.9.1 Total Inward Leakage*

(EN 149:2001+A1:2009, Clause 8.5)

Test Requirement	Results	Comment
The total inward leakage consists of three components: face seal leakage, exhalation value leakage(if exhalation value fitted) and filter penetration. For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than: 25% for FFP1, 11% for FFP2, 5% for FFP3 and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than: 22% for FFP1, 8% for FFP2, 2% for FFP3	Detail refer to Appendix 1	Meet FFP1, Meet FFP2

Appendix 1: Summarization of Test Data

Inward Leakage Test Data

Subject	Sample	Condition	Walk(%)	Head	Head	Talk(%)	Walk(%)	Mean(%)
	No.			Side/side(%)	up/down(%)			
1#	1	A.R.	6.1	6.9	7.1	7.3	6.0	6.7
2#	2	A.R.	7.0	8.0	8.6	9.0	7.5	8.0
3#	3	A.R.	6.9	7.5	8.3	8.4	6.6	7.5
4#	4	A.R.	6.8	7.7	8.4	8.6	7.4	7.8
5#	5	A.R.	6.6	7.3	7.6	8.0	6.5	7.2
6#	6	T.C.	6.6	7.6	8.5	8.6	7.1	7.7
7#	7	T.C.	5.6	6.2	6.4	7.1	5.2	6.1
8#	8	T.C.	6.1	7.0	7.3	7.6	6.3	6.9
9#	9	T.C.	5.6	6.4	6.5	7.1	5.8	6.3
10#	10	T.C.	6.0	6.7	7.3	7.5	5.7	6.6

Facial Dimension

Subject	Face length(mm)	Face Width(mm)	Face Depth(mm)	Mouth Width(mm)
1#	120	130	109	59
2#	122	140	115	65
3#	119	160	139	55
4#	112	122	119	63
5#	110	130	118	60
6#	115	119	110	59
7#	112	123	113	55
8#	103	130	100	50
9#	118	139	130	63
10#	120	135	125	50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国·上海·徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763 t (86-21) 61402666 f (86-21) 64958763



SL52035260315601TX

Date: June 15,2020 Page 4 of 9

Clause 7.9.2 Penetration of Filter Material*

(EN 149:2001+A1:2009, Clause 8.11 & EN 13274-7:2019)

Test Requirer	ment	Results	Comment	
The penetration	on of the filter of the particle filte	ring half mask shall meet th	he	
requirements	of the following table.			
Classific	a Maximum penetration	on of test aerosol		
tion	Sodium chloride test 95	Paraffin oil test 95 l/min		
	l/min		Deteil vefev to	Most EED1
	%	%	Detail refer to	Meet FFP1, Meet FFP2
	max.	max.	Appendix 2	Meet FFF2
FFP1	20	20		
FFP2	6	6		
FFP3	1	1		
	•			

Appendix 2: Summarization of Test Data

Penetration of filter material

Aerosol	Condition	Sample No.	Penetration (%)	Assessment
		11	0.2	
	As received	12	0.2	
		13	0.2]
		14	0.2]
Sodium chloride test	Simulated wearing treatment	15	0.3]
		16	0.2]
	Machanical atranath . Tamparatura	17	0.5]
	Mechanical strength +Temperature conditioned	18	0.4	Pass
	Conditioned	19	0.5	
		20	1.4	
	As received	21	1.4	
		22	1.3	
		23	1.4	
Paraffin oil test	Simulated wearing treatment	24	1.5	
	_	25	1.5	
	Machanical atranath - Tamparatura	26	4.0	
	Mechanical strength +Temperature conditioned	27	4.4	
	Conditioned	28	4.1	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035260315601TX

Page 5 of 9

Clause 7.10 Compatibility with Skin*

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
Materials that may come into contact with the wearer's skin shall not be	No irritation or	
known to be likely to cause irritation or any other adverse effect to health.	any other adverse	Pass
	effect to health	

Date: June 15,2020

Clause 7.11 Flammability*

(EN 149:2001+A1:2009, Clause 8.6)

Test Requirement	Results	Comment
The material used shall not present a danger for the wearer and shall not be	Datail refer to	
of highly flammable nature When tested, the particle filtering half mask shall not burn or not to continue	Detail refer to Appendix 3	Pass
to burn for more than 5 s after removal from the flame.		

Appendix 3: Summarization of Test Data

Flammability

Condition	Sample No.	Result	Assessment
An received	29	Burn for 0.1s	
As received	30	Burn for 0.1s	Pass
Temperature	31	Burn for 0.1s	Fass
conditioned	32	Burn for 0.1s	

Clause 7.12 Carbon Dioxide Content of The Inhalation Air*

(EN 149:2001+A1:2009, Clause 8.7)

Test Requirement	Results	Comment
The carbon dioxide content of the inhalation air (dead space) shall not	Detail refer to	Pass
exceed an average of 1.0 % (by volume)	Appendix 4	Fa55

Appendix 4: Summarization of Test Data

Carbon Dioxide Content of The Inhalation Air

Condition	Sample No.	Resu	Assessment	
	33	0.6825%		
As received	34	0.6950%	Mean value :0.69%	Pass
	35	0.6880%		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035260315601TX

Page 6 of 9

Clause 7.13 Head Harness*

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
The head harness shall be designed so that the particle filtering half mask can be donned and removed easily.	Comply	
The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in position and be capable of maintaining total inward leakage requirements for the device.	Comply	Pass

Date: June 15,2020

Clause 7.14 Field of Vision *

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The field of vision is acceptable if determined so in practical performance	Comply	Pass
tests.		1 433

Clause 7.15 Exhalation Valve(s)*

(EN 149:2001+A1:2009, Clause 8.2 & 8.9.1 & 8.3.4 & 8.8)

Test Requirement	Results	Comment
(a) A particle filtering half mask may have one or more exhalation valve(s), which shall function correctly in all orientations.	Not applicable due to exhalation valve	
(b) If an exhalation valve is provided it shall be protected against or be resistant to dirt and mechanical damage and may be shrouded or may include any other device that may be necessary for the particle filtering half mask to comply with 7.9.	Not applicable due to exhalation valve	N.A
(c) Exhalation valve(s), if fitted, shall continue to operate correctly after a continuous exhalation flow of 300 l/min over a period of 30 s.	Not applicable due to exhalation valve	
(d) When the exhalation valve housing is attached to the faceblank, it shall withstand axially a tensile force of 10N applied for 10 s.	Not applicable due to exhalation valve	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035260315601TX

Page 7 of 9

Clause 7.16 Breathing Resistance*

(EN 149:2001+A1:2009, Clause 8.9)

Test Requireme	nt		Results	Comment		
The penetration requirements of t			g half mask shall m	neet the		
Classification	Maximu	ım permitted resis			Meet FFP1,	
	Inh	alation	Exhalation		Detail refer to Appendix 5	Meet FFP2, Meet FFP3
	30 l/min	95 l/min	160 l/min			
FFP1	0.6	2.1	3.0			
FFP2	0.7	2.4	3.0			
FFP3	1.0	3.0	3.0			

Date: June 15,2020

Appendix 5: Summarization of Test Data

resistance	

As received	Flow rate		5	Бресі	men	No.3	6	Specimen No.37				Specimen No.38					
			Α	В	С	D	Е	Α	В	С	D	E	Α	В	С	D	Е
	Inhalation	30 l/min	0.4	0.5	0.4	0.5	0.5	0.4	0.4	0.4	0.4	0.4	0.5	0.4	0.5	0.4	0.4
		95 l/min	2.1	2.2	2.1	2.1	2.1	2.1	2.0	2.1	2.1	2.2	2.1	2.1	2.1	2.1	2.1
	Exhalation	160 l/min	2.5	2.5	2.4	2.5	2.4	2.5	2.5	2.5	2.4	2.5	2.6	2.4	2.5	2.5	2.5
Simulated	Flow r	ate	5	Specii	men	No.3	9	5	Specimen No.40				Specimen No.41				
wearing treatment			Α	В	С	D	Е	Α	В	С	D	E	Α	В	С	D	Е
	Inhalation	30 l/min	0.5	0.4	0.4	0.5	0.4	0.4	0.5	0.4	0.4	0.5	0.4	0.4	0.5	0.5	0.4
		95 l/min	2.1	2.2	2.1	2.1	2.1	2.1	2.2	2.1	2.1	2.1	2.1	2.2	2.1	2.1	2.2
	Exhalation	160 l/min	2.5	2.5	2.5	2.5	2.6	2.5	2.5	2.5	2.4	2.5	2.4	2.6	2.6	2.5	2.5
Temperature	Flow r	ate	5	Specii	men	No.4	2	()	Speci	men	No.4	3	S	Speci	men	No.4	4
conditioned			Α	В	С	D	Е	Α	В	С	D	E	Α	В	С	D	Е
	Inhalation	30 l/min	0.4	0.5	0.4	0.4	0.5	0.5	0.4	0.4	0.5	0.4	0.4	0.4	0.5	0.4	0.4
		95 l/min	2.2	2.2	2.2	2.1	2.0	2.1	2.2	2.2	2.1	2.1	2.1	2.2	2.1	2.1	2.1
	Exhalation	160 l/min	2.5	2.5	2.5	2.5	2.6	2.5	2.5	2.5	2.6	2.5	2.4	2.4	2.4	2.5	2.5
Assessment	·						Pass	;									

A: facing directly ahead; B: facing vertically upwards; C: facing vertically downwards; D: lying on the left side; E: lying on the right side



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐江区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86–21) 64958763 f (86–21) 64958763 www.sgsgroup.com.cn e sgs.china@sgs.com



SL52035260315601TX

Page 8 of 9

Clause 7.17 Clogging*

(EN 149:2001+A1:2009, Clause 8.9 & 8.10)

Test Requireme	<u>nt</u>	Results	Comment	
Valved particle fill After clogging the FFP1: 4 mbar, FF	eathing resistance tering half masks: e inhalation resistances shall not FP2: 5 mbar, FFP3: 7 mbar at 95 esistance shall not exceed 3 mb	Optional for single shift device only	N.A	
After clogging the	filtering half masks: e inhalation and exhalation resist FP2: 4 mbar, FFP3: 5 mbar at 95			
All types (valved	netration of filter material and valveless) of particle filter grequirement shall also meet the			
Classificatio	Maximum penetration	n of test aerosol		
n	Sodium chloride test 95 l/min	Paraffin oil test 95 l/min	Optional for single	N.A
	%	%	shift device only	
	max.	max.		
FFP1	20	20		
FFP2	6	6		

Date: June 15,2020

Clause 7.18 Demountable Parts

(EN 149:2001+A1:2009, Clause 8.2)

(=:::::::::::::::::::::::::::::::::::::		
Test Requirement	Results	Comment
All demountable parts (if fitted) shall be readily connected and secured,	Comply	Pass
where possible by hand		F a 5 5

Test	Uncertainty
Total inward leakage	2.98%
Penetration of filter material	1.00%
Flammability	1.00%
Carbon dioxide content of the inhalation air	0.93%
Breathing resistance	1.90%

*: This test standard is carried out by external laboratory accredited by CNAS (China National Accreditation Service for Conformity Assessment) L10118.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035260315601TX

Page 9 of 9

Sample Photo

Date: June 15,2020



End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐江区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763 t (86-21) 61402666 f (86-21) 64958763 www.sgsgroup.com.cn e sgs.china@sgs.com